

(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: **09153882 A**

(43) Date of publication of application: **10.06.97**

(51) Int. Cl.
H04J 11/00
H04J 1/20
H04L 27/34

(21) Application number: **08043854**

(22) Date of filing: **29.02.96**

(30) Priority: **25.09.95 JP 07246431**

(71) Applicant: **VICTOR CO OF JAPAN LTD**

(72) Inventor: **KANEKO KEIICHI**

(54) **ORTHOGONAL FREQUENCY DIVISION
MULTIPLE SIGNAL TRANSMISSION SYSTEM,
TRANSMITTING DEVICE AND RECEIVING
DEVICE**

circuit 314. Thus, a high speed change characteristic can be corrected.

COPYRIGHT: (C)1997,JPO

(57) Abstract:

PROBLEM TO BE SOLVED: To prevent the occurrence of a code error by correcting the error of an amplitude character difference and a phase characteristic difference between an I-signal and a Q-signal.

SOLUTION: A transmission side transmits a known reference signal with a specified carrier among plural carriers constituting an OFDM signal, designates the carrier transmitting the known reference signal by a symbol number transmitted with the prescribed carrier, and sequentially changes and transmits them in a circle at every regular period. A reception side demodulates the reference signal in a decoding circuit 311 and a detection circuit 312 detects a transmission line characteristic. A first correction expression deviation holding circuit 313 calculates and stores a first correction expression from the detected transmission line characteristic. A first correction circuit 314 decodes the signals by using the correction expression. A second correction expression is newly calculated and corrected for the output signal of the correction

